



AC BRUSHLESS SERVOMOTORS - DSM5.4x



DSM5 - size FOUR Brushless Servomotors are AC PM Synchronous servomotors. They have been designed using the latest generation of magnets and construction techniques to provide very high performance, low cogging and torque ripple. They can be supplied with resolver or Incremental / absolute encoder.


Their main characteristics are:

- Frame size 115 mm
- Rare earth magnets for high performance
- 8 pole construction for high torque density
- Low cogging and torque ripple
- Sinusoidal back EMF
- Integrated PTC thermal protection
- Rotatable connectors
- Compact design
- High IP rating
- Smooth finish

Technical Data

Tab .1

Description Winding code	Symbol	Motor	DSM5.41		DSM5.42		DSM5.43	
		Units	1	2	1	2	1	2
Stall Torque	M_0	Nm	4,0		7,6		11,3	
Maximum Torque	M_{pk}	Nm	14		26		39	
Stall Current	I_0	A	4,4	2,5	7,8	4,7	12	7,0
Peak current	I_{pk}	A	18	10	31	19	48	29
Maximum mechanical revs	N_{mec}	min^{-1}	6500		6500		6500	
Maximum revs @ 230Vac	N_{MAX}	min^{-1}	3200	1800	3100	1800	3200	1800
Maximum revs @ 400Vac	N_{MAX}	min^{-1}	6000	3000	5000	3000	5000	3000
Voltage constant	K_E	V/krpm	55	96	59	98	59	98
Torque constant	K_T	Nm/A	0,91	1,59	0,98	1,62	0,98	1,62
Rotor Inertia	J_R	$kg\ cm^2$	5		9,6		14	
Resist. @ 20°C	R_{U-V}	Ohm	2,3	6,9	0,95	2,7	0,5	1,5
Induct. @ 1 kHz	L_{U-V}	mH	5,6	17,9	3,8	10,7	2,5	6,9
Mass	m	kg	5,6		8,5		11,4	



Dimension in mm

Tab. 2

Feedback device	EQI1131, TTL 2048ppr, Resolver			SinCos, SKM36		
Dimension	LB	L01	L03	LB	L01	L03
DSM5.41	146,5	123,5	32	160,5	137,5	46
DSM5.42	186,5	163,5		200,5	177,5	
DSM5.43	226,5	203,5		240,5	217,5	
DSM5.41 Brake	195,5	172,5		209,5	186,5	
DSM5.42 Brake	235,5	212,5		249,5	226,5	
DSM5.43 Brake	275,5	232,5		289,5	246,5	

Dimension in mm

Tab. 3

Shaft	Dimension	
D	19j6	24j6
E	40	50
GL	32	32
GA	21,5	27
F	6	8
R	M6 x 16	M8 x 15

INFORMATION - Bold data refers to standard version dimensions.

The following accessories are available on request:

- | | |
|---|---|
| <ul style="list-style-type: none"> • IP65 enclosure protection with shaft seal • Max ambient temperature 40° C • Min ambient temperature 0 °C • Max Altitude 1000 m (above sea level) • Insulation class F (materials F & H) • RMS values | <ul style="list-style-type: none"> • Insulation system conforms to UL • Motor Installation B5 – V5 • Cooling IC410 • Typical tolerance value $\pm 10\%$ • Continuous ratings apply with a rise of $\Delta T = 100K$ on the windings when fitted on an aluminium plate with dimensions 305 x 305 x 15mm |
|---|---|

Sangalli reserves the right to amend the specification of this product without prior notification.

PART NUMBER COMPOSITION

1	2	3	4	5	6	7	8	9	10	11	12
D	S	M	5	4	2	2	0	4	7	x	x

POS. DESCRIPTION

- 1-3 **Product**
DSM = PM synchronous motor, self-cooled
- 4 **Motor type**
Series 5
- 5 **Motor size**
Size Four
- 6 **Motor length**
1 = Mo 4 Nm
2 = Mo 7,6 Nm
3 = Mo 11,3 Nm
- 7 **Voltage**
1 = Winding code 1
2 = Winding code 2
- 8 **Holding brake**
0 = Without brake
1 = Permanent Magnet Brake $24V_{DC} \pm 6\%$ $M_{br} = 18Nm$ $24W$ $J_{br} = 2,4 \text{ kgcm}^2$ $m = 1,4kg$
- 9 **Feedback**
0 = Sensorless
3 = Heidenhain Encoder EQI1131 Endat Multi Turn 2.2
4 = Incremental Encoder 2048 PPR + hall
6 = Incremental Encoder 4096 PPR + hall
7 = Encoder sin-cos 1 Vpp 2048 with CD channels
9 = Resolver 2p 7V 10KHz
W = Sick encoder EKS36 18bit NO SIL, DSL
Y = Sick encoder EKM36 18bit Multi turn NO SIL, DSL
Z = Sick encoder SKM36 Hiperface 128i PPT Multi turn

Available on request SIL option on some types of encoders
- 10 **Connection type**
7 = M23 90° 6 poles power connector / M23 90° feedback
- 11-12 **Special version** (Below some examples, for further details please contact our technical support.)
24 = Shaft 24 x 50
26 = Shaft without key
66 = IP65 Shaft Protection
90 = Thermal protection PT1000
xx = Special Shaft and Flanges (on request)



SANGALLI SERVOMOTORI

MOTORS & MOTION CONTROL

DSM5 BRUSHLESS SERVOMOTORS

DSG SYNCHRONOUS PM GENERATORS

RARE EARTH SC DC SERVOMOTORS

DSW WATER-COOLED

LOW-COST SOLUTIONS

PLANETARY GEARS

CUSTOMISED SOLUTIONS

TORQUE MOTORS

FRAMELESS SPINDLE MOTORS



SANGALLI SERVOMOTORI S.r.l.

Gruppo ESAUTOMOTION SPA

STRADA DEI BOSCHI, 10 - 20852 - VILLASANTA (MB) – ITALY

TEL. 1: +39 039 2020322 - TEL. 2: +39 039 2020747

EMAIL: INFO@SANGALLISERVOMOTORI.IT

WEB: WWW.SANGALLISERVOMOTORI.IT

